

Persefose 6FF

1. Basic product information

Persefose 6FF is a highly cross-linked (cross-linking ratio is 6%) agarose-based gel filtration chromatography resin, which separates different molecules by using their molecular weight and conformation differences. This chromatographic resin can be used successfully for the separation and purification of various biological molecules such as recombinant proteins, antibodies, nucleic acids, viruses and virus-like particles, and polysaccharides.

Persefose 6FF has excellent scale-up capabilities:

- (1) It has a highly cross-linked agarose matrix with excellent rigidity. On the one hand, the restriction on column bed height is reduced; on the other hand, high process flow rate can be achieved under low back pressure, improving process efficiency.
- (2) An improved bead-making process achieves a smaller diffusion effect and provides better resolution.

2. Chromatography resin parameters

Resin type	Gel filtration
Matrix	High degree cross-linking agarose 6%
Median particle size	45~165 μm
Separation range for spherical molecules	10 ~4,000 kDa
Separation range for linear molecules	10 ~2,000 kDa
Recommended flow rate	90~200 cm/h*
Maximum flow rate	300 cm/h
Maximum working pressure	3 bar
Working temperature	4–30°C

* When the height of the column bed is ≥ 60 cm, it is recommended that the flow rate is reduced to 45~60 cm/h.

3. Chemical resistance

pH stability*	2–14
Chemical stability	All commonly used aqueous buffers, 30% isopropanol**, 75% ethanol**, 1M NaOH, 1M acetic acid, 6M guanidine hydrochloride, 8M urea

* The physical and chemical properties and functions of the chromatographic resin have no obvious changes after being placed in an environment of 40°C and pH 2–14 for 7 days.

** v/v , volume ratio

4. Method of use

4.1 Chromatographic conditions

- (1) Buffer selection: the stability of the sample in the buffer should be considered; to avoid possible non-specific adsorption, it is advisable to use a salt-containing buffer instead of ultra pure or pure water.

(2) Flow rate: according to the height of the column bed, a linear flow rate of 90~200 cm/h is generally selected.

(3) Sample pretreatment: to prevent the sample from clogging the column, it needs to be filtered with a 0.45 µm microporous membrane before loading.

4.2 Chromatography steps

(1) Equilibration: use the buffer to fully equilibrate the chromatography column until the pH and conductivity are stable and basically the same as the equilibration buffer. This step usually requires 1–2 column bed volumes (CV).

(2) Sample loading: the usual loading volume is 1%–5% CV, and the sample concentration should not be too high, to avoid overpressure or affecting the resolution.

(3) Elution: use buffer to elute, and collect peaks at different positions, usually requiring 1~1.5 CV.

(4) Regeneration: rinse the column with a buffer containing high salt (such as 1M NaCl).

(5) Re-equilibration: re-equilibrate the column with buffer.

5. Cleaning and regeneration

Contaminants (e.g. lipids, endotoxins and proteins) accumulate on the column as the number of uses of the chromatography resin increases. Regular cleaning-in-place (CIP) is essential to keep the column in a stable working condition. Determine the frequency of CIP according to the degree of contamination of the chromatography resin (if the contamination is considerable, CIP is recommended after each use to ensure repeatability of results and to prolong the working life of the chromatography resin).

For different types of impurities and contaminants, the recommended cleaning conditions are as follows:

- Removal of strongly binding proteins: wash with 5 CV of 2M NaCl solution or use a high salt buffer not lower than pH 2, such as 1M NaAc solution.
- Removal of strongly hydrophobic proteins and precipitated proteins: first wash with 5 CV of 1M NaOH solution, then wash the lye with 5–10 CV of ultra pure or pure water.
- Removal of lipoproteins and lipids: first wash with 5 CV of 70% ethanol or 30% isopropanol, then rinse with 5–10 CV of ultra pure or pure water.

Note: 70% ethanol or 30% isopropanol should be degassed before use; the flow rate should be 30–60 cm/h during CIP; reverse cleaning should be used when the clogging is severe.


To reduce the microbial load, it is recommended that 0.5~1M NaOH solution is used to treat the chromatography resin; treatment time is 15–30 minutes.

6. Storage

Keep the unopened chromatography resin in the original container and store at 4~30°C in a well-ventilated, dry and clean place. Do not freeze. Wash the used column with 2–3 CV of 20% ethanol solution and store at 2~8°C.

7. Destruction and recycling

Since chromatography resin is difficult to degrade in nature, it is recommended that the waste chromatography resin is incinerated to protect the environment. For chromatography resin that has been in contact with biologically active samples such as viruses and blood, follow the local biosafety requirements before destroying or disposing of it.



LT BIOTECH UAB
Mokslininkų g. 6A,
LT-08412 Vilnius,
Lithuania
www.ltbiotech.lt

8. Packing method

Detailed information on resin packaging is available on request. Please contact your local distributor.

9. Ordering information

Product name: Persefose 6FF

Product Cat. No	Package
702-00025	25 ml
702-00100	100 ml
702-00500	500 ml
702-01000	1 L
702-05000	5 L
702-10000	10 L
702-20000	20 L